










HPS3-1U-MXX

rackmount server



SPECIFICATION

							
Xeon E Series - 6 core	16GB DDR4 ECC Server Memory	ONBOARD	VGA x1	2 x 1GbE LAN	1 x 250GB JBOD	Up to 60TB R5	Win Server 2019 64bit
RAID CONTROLLER	RAID BATTERY BACKUP	RAID CONFIG	REDUNDANT PSU	PSU	FORM FACTOR	IPMI REMOTE MANAGEMENT	ACCESSORIES
hardware	YES	JBOD RAID5	Yes Hot-Swappable	300W, 80 Plus Certified Gold	1U RACKMOUNT	YES	Rack-mount kit KB and mouse 2 x Power Cables

TECHNICAL

Electrical	Physical	Environmental
100 - 240V, 50 - 60Hz CERTIFICATES: FCC, CUL, CE, EN60501/IEC-60950	DIMENSIONS: WIDTH: 437mm DEPTH: 550mm HEIGHT: 43mm WEIGHT: 17Kg	OPERATING TEMP: 0C to 35C STORAGE TEMP: -40C to 60C HUMIDITY RANGE: 10% to 90% non-condensing
Reference *: SSD = Solid State Disk, HDD = Hard Disk Drive, GB = Gigabyte (1000 Megabytes), TB = Terabyte (1000 Gigabytes), R1 = RAID1, R5 = RAID5, R6 = RAID6, R50 = RAID50, R60 = RAID60, +HS = Hotspare, 1GbE = 1 Gigabit Ethernet, 10 GbE = 10 Gigabit Ethernet, SFP / SFP+ = Fibre network connection, CPU = Central Processing Unit, GPU = Graphics Processing Unit, OS = Operating System, IPMI = Remote out of band management, KB = Keyboard		

