HPC-CTD-1U-H12700R32S1T101

rackmount server

SECURE LOGIQ

SPECIFICATION

CPU		GPU	OUTPUT	NET	SSD		OS
Intel 12th Gen i7-12700	32GB DDR4 Memory	nVidia T1000 - 4GB	4 x miniDP	2 x 1GbE LAN	1 x 250GB JBOD	None	Win 10 Pro 64bit

RAID CONTROLLER	RAID BATTERY BACKUP	RAID CONFIG	REDUNDANT PSU	PSU	FORM FACTOR	IPMI REMOTE MANGEMENT	ACCESSORIES
none	No	JBOD	Yes Hot-Swappable	Redundant 1+1, 80 Plus Certified Gold	1U Rackmount	No	Power cables Rack-mount kit Keyboard and mouse

TECHNICAL

Electrical	Physical	Enviromental
100 - 240V, 50 - 60Hz CERTIFICATES: FCC, CUL, CE, EN6050/IEC-60950	DIMENSIONS: WIDTH: 437mm DEPTH: 550mm HEIGHT: 43mm WEIGHT: 17Kg	OPERATING TEMP: 0C to 35C STORAGE TEMP: -40C to 60C HUMIDITY RANGE: 10% to 90% non-condensing

Reference *:
SSD = Solid State Disk, HDD = Hard Disk Drive, GB = Gigabyte (1000 Megabytes), TB = Terabyte (1000 Gigabytes), R1 = RAID1, R5 = RAID5, R6 = RAID6, R50 = RAID50, R60 = RAID60, +HS = Hotspare, 1GbE = 1 Gigabit Ethernet, 10 GbE = 10 Gigabit Ethernet,SFP / SFP+ = Fibre network connection, CPU = Central Processing Unit, GPU = Graphics Processing Unit, OS = Operating System, IPMI = Remote out of band management, KB = Keyboard

Doc Version 3.0